



NB5Q-TW01B-V1

NB-V1 HMI with a 5.6 Inch display and a Black Bezel and Ethernet + USB Host

Specifications

Screen diagonal	5.6 in
Number of pixels, horizontal	320
Number of pixels, vertical	240
Type of display	TFT
Frame color	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colors of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	184 mm
Height of the front	142 mm
Width of panel cutout	172.4 mm
Height of panel cutout	131 mm
Built-in depth	46 mm
Product Weight (unpacked)	660 g

Accessories



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

Downloads

CAD Library



EVE CR-series button cells
Battery Safety Datasheet

EN PDF 380 KB



How to Import PLC Variables from Sysmac Studio
Practice Guide

EN PDF 534 KB



NB Faceplate 5.0 - Multilanguage
Software

EN ZIP 75.9 MB



NB Series Programmable Terminal
Brochure

EN PDF 4.23 MB



NB-Designer Setup v1.6.7.0
Software

EN EXE 506 MB



NB-Series
Getting Started Guide

EN PDF 11.9 MB



NB-Series
Setup Manual

EN PDF 9.74 MB



NB-Series Host Connection
Setup Manual

EN PDF 14.6 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 15 September, 2026. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)