



S8VK-S12024

Book type power supply, 120 W, 24VDC, 5A, DIN rail mounting, Push-in terminal, Coated

Specifications

Type	DIN-rail
Mounting method	DIN rail
Phase	Single
Output voltage	24 V
Power output	120 W
Rated output current	5 A
Efficiency	92 %
Power boost ratio	120 %
Temperature range	-40-70 °C
Features	Coated
Terminal type	Push-in
Communication port(s)	None
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	55 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	90 mm

Accessories



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

Related products



S8V-NF
Noise Filter S8V-NF



Electronic Circuit Breaker
S8V-CP - Electronic Circuit Breaker

Downloads

CAD Library



Perfect Power Supply Solutions
Brochure

EN PDF 1.29 MB



S8VK-S Switch Mode Power Supply
Datasheet

EN PDF 5.79 MB



S8VK-S/S8FS-G
Brochure

EN PDF 2.4 MB



Solution case study No.8 Environment resistance
Brochure

EN PDF 623 KB



T235 Emea S8vk Series Switch Mode Power Supplies
Brochure

EN PDF 1.75 MB



Value Design for Panel
Flyer

EN PDF 3.86 MB

